







Energy efficiency benefits from lighting, residential refrigerators, room air conditioners, power and distribution transformers and industrial electric motors with the implementation of globally benchmarked minimum energy performance standards.

### ANNUAL SAVINGS IN 2030

↓ <b>•</b> 	Reduce electricity use	
	→ by over 60 GWh	
	→ 7.2% of future national electricity use	
ààà	Save electricity worth <b>7 Million USD</b>	
	equivalent to <b>1 Power Plants [20MW]</b>	
<b>CO</b> <sub>2</sub>	Reduce CO <sub>2</sub> emissions by 40 Thousand Tonn	ies
	equivalent to 20 Thousand Passenger Cars	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~



EVEN GREATER SAVINGS POSSIBLE WITH BEST AVAILABLE TECHNOLOGY



# THE PATHWAY TO ENERGY EFFICIENCY



ANNUAL SAVINGS IN 2025 AND 2030

		Lighting		ĺ				<u>Ľ</u>			
					ential erators	Room Air Conditioners		Transformers		Industrial Electric Motors	
		2025	2030	2025	2030	2025	2030	2025	2030	2025	2030
	Electricity (GWh)	18.7	22.2	6.6	15.1	1.5	2.8	7.4	15.5	2.0	4.0
ààà	Electricity Bills (thousand US\$)	2,108.7	2,507.7	750.3	1,711.2	167.2	316.3	840.4	1,748.4	228.0	451.9
CO <sub>2</sub>	CO2 Emissions (thousand tonnes)	12.7	15.1	4.5	10.3	1.0	1.9	4.6	9.5	1.4	2.7

### CUMULATIVE SAVINGS (2020 - 2030)

		Lighting	Residential Refrigerators	Room Air Conditioners	<b>Transformers</b>	Industrial Electric Motors
	Electricity (GWh)	171.1	77.1	16.0	85.6	22.1
ففف	Electricity Bills (million US\$)	19.3	8.7	1.8	9.7	2.5
CO <sub>2</sub>	CO2 Emissions (thousand tonnes)	116.1	52.3	10.8	52.7	15.0

OTHER BENEFITS IN 2030						
*	k K	Direct GHG emissions reduced by	<b>→</b>	7 Thousand Tonnes		
		Increased grid connection to	<b>→</b>	30 Thousand Households		

## ENERGY EFFICIENCY STRATEGY AND NATIONALLY DETERMINED CONTRIBUTION

Country Nationally Determined Contribution (NDC): Unconditional contribution of 3% reduction of emissions of greenhouse gases compared to 2005 (BAU) by 2030.Conditional contribution of 20% reduction of emissions compared to 2005 BAU by 2030.

## **Country Specific Data and Input** Assumptions

## For Burundi



GENERAL INFORMATION				ELECTRICITY MARKET				
Population	11.2 million		Residential Electricity tariff		0.113 US\$ / kWh			
GDP per capita	734 US\$		Industrial Electricity tariff		0.113 US\$ / kWh			
Electrification level	10%		Transmission and		9.18%			
CO2 Emission Factor	0.616 kg / kWh		distribution loss factor					
ASSUMPTIONS								
Product	Unit Energy Consumption (kWh/year) or Efficiency Level				The floor had			
Product	BAU	Policy Scenario		BAT	Type of Product			
Lighting	65.7	15.3		8.8	Low incandescent Lamp,3h/day; 14W CFL; 8W LED			
Residential Refrigerators	350	191		134	2-door top-mount Average size 225 liters			
Room Air Conditioners	1,626	1,326		869	Split unit with 3.5 kW cooling capacity			
Transformers	N/A	SEAD Tier3		SEAD Tier5	three-phase and single-phase liquid- filled and three-phase dry-type power and distribution transformer			
Industrial Electric Motors	IE1/IE0	IE3	8	IE4	3-phase induction motors Ranging from: 0.75 - 7.5 kW; 7.5 - 75 kW;75 - 375 kW			

#### METHODOLOGY

The analysis uses CLASP's and Lawrence Berkeley National Laboratory's Policy Analysis Modeling System (PAMS) to forecast the impacts from implementing policies that improve the energy efficiency of new household air conditioners and refrigerators. For lighting, electric motors, and power and distribution transformers individual - models were developed, taking into account country level data, expected GDP growth, and industrialization levels. The savings potential assumes minimum energy performance standards (MEPS) are implemented in 2020 at level equivalent to the present day (2015) best global MEPS that are currently implemented. The graph on page two also shows the savings potential that is possible with the implementation of MEPS in 2020 at level equivalent to the present day best available technology (BAT).

#### ASSUMPTIONS AND DATA SOURCES

- Population and GDP per capita data (2014) comes from the World Bank.
- Electrification levels come from the International Energy Agency (IEA).
- Market size was determined by data provided by industry partners; UN Comtrade database; household penetration forecasts generated by PAMS from population, climate, and macroeconomic indicators.
- E Future electricity consumption was calculated using current consumption figures provided by the IEA and the U.S. Energy Information Administration (EIA).
- Baseline price, unit energy consumption (UEC), appliance lifetime were provided by country representatives (when available); industry partners; and Lawrence Berkeley National Laboratory. The business-as-usual scenario assumes a 1 per cent annual improvement in UEC.
- Electricity tariffs were provided by the IEA; and Internet research.
- Transmission and distribution loss factor is a regional average calculated from electricity production and consumption data published by the IEA.
- CO2 emission factor came from the IEA and extrapolations were made for countries lacking data.
- Consumer discount rate was derived from the Human Development Index, United Nations Development Programme (2012).
- The approach of calculating the potential direct emission saving of refrigerators and air conditioners: the typical current mix of refrigerants fillings, leakage rates and end of life anisotropy in the DAM expression of the base based on the based of the based o
- life emissions in the BAU compared to the best alternative with natural refrigerants (mostly R290 for splits and R600a for domestic refrigerators).
- Additional to the above sources, a questionnaire was used to gather data from country officials.









