







Energy efficiency benefits from lighting, residential refrigerators, room air conditioners, power and distribution transformers and industrial electric motors with the implementation of globally benchmarked minimum energy performance standards.

ANNUAL SAVINGS IN 2030

| | Reduce electricity use | |
|------------------------|---|--------------------------|
| | → by over 5 TWh | |
| | → 8.2% of future national electricity use | |
| ààà | Save electricity worth 610 Million USD | |
| | equivalent to 11 Power Plants [100MW] | |
| CO ₂ | Reduce CO ₂ emissions by 2 Million Tonnes | |
| | equivalent to 840 Thousand Passenger Cars | ക്കു കു കു എ കു കു കു |



EVEN GREATER SAVINGS POSSIBLE WITH BEST AVAILABLE TECHNOLOGY



THE PATHWAY TO ENERGY EFFICIENCY



ANNUAL SAVINGS IN 2025 AND 2030

| | | V Lighting | | Residential Refrigerators | | Room Air Conditioners | | 7 ransformers | | Industrial Electric Motors | |
|-----|-------------------------------------|-------------------|---------|------------------------------|---------|--------------------------|-------|----------------------|-------|-------------------------------|---------|
| | | 2025 | 2030 | 2025 | 2030 | 2025 | 2030 | 2025 | 2030 | 2025 | 2030 |
| | Electricity (GWh) | 1,084.5 | 1,107.3 | 648.5 | 1,292.4 | 183.3 | 331.2 | 474.5 | 897.5 | 515.0 | 1,097.6 |
| ففف | Electricity Bills (million US\$) | 158.3 | 161.7 | 94.7 | 188.7 | 26.8 | 48.4 | 69.3 | 131.0 | 36.0 | 76.8 |
| CO2 | CO2 Emissions (thousand tonnes) | 359.6 | 367.1 | 215.0 | 428.5 | 60.8 | 109.8 | 132.9 | 251.3 | 170.7 | 363.9 |

| CUMULATIVE SAVINGS (2020 - 2030) | | | | | | | | |
|----------------------------------|-------------------------------------|----------|------------------------------|--------------------------|--------------|-------------------------------|--|--|
| | | 4 | Ī | | <u>*</u> | | | |
| | | Lighting | Residential Refrigerators | Room Air Conditioners | Transformers | Industrial Electric Motors | | |
| | Electricity (TWh) | 9.5 | 7.1 | 1.9 | 5.3 | 5.8 | | |
| ففف | Electricity Bills (billion US\$) | 1.4 | 1.0 | 0.3 | 0.8 | 0.4 | | |
| CO ₂ | CO2 Emissions (million tonnes) | 3.1 | 2.4 | 0.6 | 1.5 | 1.9 | | |

| OTHER BENEFITS IN 2030 | | | | | | |
|------------------------|--|-------------|----------------|--|--|--|
| * | Direct GHG emissions reduced by | → 2 Million | Tonnes | | | |
| <u> </u> | Reduced emissions by \rightarrow SO2 | 470 Tonnes | NOx 254 Tonnes | | | |

ENERGY EFFICIENCY STRATEGY AND NATIONALLY DETERMINED CONTRIBUTION

Country Nationally Determined Contribution (NDC): An unconditional 20% reduction in emissions by 2030, compared to business as usual. A 30% reduction is offered conditional on international funding. This would equate to a 22% increase compared to 2010 emissions.

Country Specific Data and Input Assumptions



For Peru

| GENERAL INFORMATION | | | | ELECTRICITY MARKET | | | | |
|----------------------------|----------------------|-----------------|--------------------------------|--------------------|--|--|--|--|
| Population | 30.8 million | | Residential Electricity tariff | | 0.146 US\$ / kWh | | | |
| GDP per capita | 6,594 US\$ | | Industrial Electricity tariff | | 0.070 US\$ / kWh | | | |
| Electrification level | 91% | | Transmission and | | 15.55% | | | |
| CO2 Emission Factor | 0.28 kg / kWh | | distribution loss factor | | | | | |
| ASSUMPTIONS | | | | | | | | |
| Due duet | Unit Energy Co | onsumption | (kWh/year) or Efficiency Level | | | | | |
| Product | BAU | Policy Scenario | | ВАТ | Type of Product | | | |
| Lighting | 65.7 | 15.3 | 3 | 8.8 | Low incandescent Lamp,3h/day; 14W CFL; 8W LED | | | |
| Residential Refrigerators | Refrigerators 485 21 | | 2 | 163 | 2-door top-mount Average size 300 liters | | | |
| Room Air Conditioners | 813 | 663 | 3 | 434 | Split unit with 3.5 kW cooling capacity | | | |
| Transformers | N/A | SEAD Tier3 | | SEAD Tier5 | three-phase and single-phase liquid- filled and three-phase dry-type power and distribution transformers | | | |
| Industrial Electric Motors | IE1/IE0 | IE3 | | IE4 | 3-phase induction motors Ranging from: 0.75 - 7.5 kW; 7.5 - 75 kW;75 - 375 kW | | | |

METHODOLOGY

The analysis uses CLASP's and Lawrence Berkeley National Laboratory's Policy Analysis Modeling System (PAMS) to forecast the impacts from implementing policies that improve the energy efficiency of new household air conditioners and refrigerators. For lighting, electric motors, and power and distribution transformers individual - models were developed, taking into account country level data, expected GDP growth, and industrialization levels. The savings potential assumes minimum energy performance standards (MEPS) are implemented in 2020 at level equivalent to the present day (2015) best global MEPS that are currently implemented. The graph on page two also shows the savings potential that is possible with the implementation of MEPS in 2020 at level equivalent to the present day best available technology (BAT).

ASSUMPTIONS AND DATA SOURCES

- Population and GDP per capita data (2014) comes from the World Bank.
- Electrification levels come from the International Energy Agency (IEA).
- Market size was determined by data provided by industry partners; UN Comtrade database; household penetration forecasts generated by PAMS from population, climate, and macroeconomic indicators.
- Future electricity consumption was calculated using current consumption figures provided by the IEA and the U.S. Energy Information Administration (EIA).
- Baseline price, unit energy consumption (UEC), appliance lifetime were provided by country representatives (when available); industry partners; and Lawrence Berkeley National Laboratory. The business-as-usual scenario assumes a 1 per cent annual improvement in UEC.
- Electricity tariffs were provided by the IEA; and Internet research.
- Transmission and distribution loss factor is a regional average calculated from electricity production and consumption data published by the IEA.
- CO2 emission factor came from the IEA and extrapolations were made for countries lacking data.
- Consumer discount rate was derived from the Human Development Index, United Nations Development Programme (2012).
- The approach of calculating the potential direct emission saving of refrigerators and air conditioners: the typical current mix of refrigerants fillings, leakage rates and end of life emissions in the BAU compared to the best alternative with natural refrigerants (mostly R290 for splits and R600a for domestic refrigerators).
- ine emissions in the BAU compared to the best alternative with natural rerigerants (mostly R290 for splits and R600a for domestic rerigerants)
- Additional to the above sources, a questionnaire was used to gather data from country officials.









