Sierra Leone




Lighting




Energy efficiency benefits from the transition to energy efficient lighting in the residential, commercial, industrial and outdoor sectors for all major lamp types through the implementation of Minimum Energy Performance Standards at two levels of ambition (minimum and high).

ANNUAL SAVINGS IN 2030*



EVEN GREATER SAVINGS POSSIBLE WITH MORE STRINGENT REGULATION






ANNUAL SAVINGS IN 2030 AND 2040*

| | | Residential | | Professional | | Outdoor | |
|----------|-------------------------------------|-------------|------|--------------|------|---------|------|
| | | 2030 | 2040 | 2030 | 2040 | 2030 | 2040 |
| ٢ | Electricity (GWh) | 2.3 | 0.2 | 18 | 1.4 | 7.3 | 0.6 |
| <u>+</u> | Electricity Bills (Million US\$) | 0.8 | 0.1 | 6.4 | 0.5 | 2.6 | 0.2 |
| | CO2 Emissions (Thousand tonnes) | 1.5 | 0.1 | 12 | 0.9 | 4.7 | 0.4 |

CUMULATIVE SAVINGS BY 2030 AND 2040*

| | | Residential | | Professional | | Outdoor | |
|----------|-------------------------------------|-------------|------|--------------|------|---------|------|
| | | 2030 | 2040 | 2030 | 2040 | 2030 | 2040 |
| 4 | Electricity (GWh) | 28 | 36 | 220 | 280 | 89 | 110 |
| <u>+</u> | Electricity Bills (Million US\$) | 10 | 13 | 78 | 100 | 32 | 41 |
| | CO2 Emissions (Thousand tonnes) | 18 | 23 | 140 | 180 | 58 | 74 |

CONTRIBUTION TO CUMULATIVE ELECTRICITY USE BY 2040



Country Data and Input Assumptions



GENERAL INFORMATION

| ELEC | FRICIT | Υ ΜΑ | RKE |
|------|---------------|------|-----|
| | | | |

| Population | 7.72 Million | Residential Electricity tariff | 0.36 US\$ / kWh |
|-----------------------|---------------|--------------------------------|-----------------|
| GDP per capita | 523 US\$ | Transmission and | 38.0% |
| Electrification level | 23.3% | distribution loss factor | |
| CO2 Emission Factor | 0.40 kg / kWh | | |

ASSUMPTIONS

| | Unit Energy Consumption (kWh/year) | | | | |
|--------------------------|------------------------------------|----------------------|------------------------------|---------------------------|----------------------------------|
| Product | Legacy | Business As Usual | Minimum Ambition Scenario | High Ambition Scenario | Type of Product |
| General Service Lighting | 60W lamp | 15W CFL | 10W LED | 7W LED | 800 lumen light bulb burning |
| (domestic use) | 60 | 15 | 10 | 7 | for 1,000 hrs/year |
| Linear Lighting | 40W T12* | <i>36W T8</i> | 20W LED | 16W LED | 4 foot tube burning for |
| (commercial use) | 120 | 108 | 60 | 48 | 3,000 hrs/year |
| HID Lighting | 70W HPS | 70W HPS | 50W LED | 40W LED | Poletop street light burning for |
| (residential roads) | 307 | 307 | 219 | 175 | 4,380hrs/year** |

*still used in emerging markets ** LED has 2 to 3 times the life & better colour

METHODOLOGY

The analysis uses the UNEP-U4E's Country Savings Assessment Models to estimate the impacts of implementing policies that improve the energy efficiency of lighting in the residential, commercial and outdoor sectors. The savings potential in each scenario assumes Minimum Energy Performance Standards (MEPS) are introduced in 2020 at two different levels of ambition (minimum and high) as shown above.

ASSUMPTIONS AND DATA SOURCES

Market size was estimated using a combination of stock estimates from multiple sources and a top-down estimate of the electricity used for lighting in each country. Electricity savings over time are calculated by estimating the impact on the overall efficacy of the lighting stock caused by transitioning to efficient lamps at different rates in each scenario. The analysis includes the following data:

• Current total electricity consumption comes from the World Bank and the U.S. Energy Information Administration (EIA). Future electricity demand is based on forecasts from the IEA's World Energy Outlook 2018.

- Population (2018 and future forecasts) comes from the UN Population Division.
- Residential electricity tariffs are based on IEA data.
- Transmission and distribution loss factor is a regional average calculated from electricity production and consumption data published by the IEA.
- Electrification levels come from the IEA's Word Energy Outlook 2018 and the World Bank.
- Transmission and distribution loss factor is a regional average calculated from electricity production and consumption data published by the IEA.
- CO2 emission factors come from the IEA and the Institute of Global Environmental Strategies (IGES) and are assumed constant in future years.

Baseline wattages, efficacies, operating hours and appliance lifetimes for each technology in each country are based on analysis from the UNEP U4E Model Regulation Guidelines and data provided by country representatives (when available) and product experts.

Additional to the above sources, a questionnaire was used to gather data from country officials.

In a small number of instances, additional data was obtained from internet research or by using proxy data from similar markets.

Further details of the modelling approach and assumptions are available on the U4E website. For more information contact: U4E@un.org





